



MIKRON³

Advanced ground microphone system for locating water leaks on site

SENSOR SPECIFICATION	Listening Rod	Ground Microphone	Accelerometer
Sensor type	Ceramic piezoelectric	Ceramic piezoelectric within windproof rubber housing	Accelerometer
Sensitivity	20V/g	20V/g	10V/g
Frequency response	10 – 5000 Hz	10 – 5000 Hz	10 – 5000 Hz
Cable length	N/A	N/A	2 m
Wireless Communications			
Type	Purepath™ (trademark of Texas Instruments)	Purepath™ (trademark of Texas Instruments)	N/A
Operating frequency	2.4GHz (ISM band)	2.4GHz (ISM band)	N/A
Output power	5dBm / 3.1mW	5dBm / 3.1mW	N/A
Wireless operating range	≤6 metres	≤6 metres	N/A
Power			
Type	Nickel Metal Hydride (rechargeable)	Nickel Metal Hydride (rechargeable)	N/A
Operating life	≥10 hours continuous use from full charge	≥10 hours continuous use from full charge	N/A
Environmental			
Operating temperature	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C
Maximum humidity	90%	90%	100%
Water ingress protection	IP65	IP65	IP68
Dimensions	235 x 45 mm diameter	170 x 180mm diameter	175 x 40mm diameter (body, no cable)
Weight	0.7kg (without rods)	1.85kg (without handle)	0.6kg (with 2m cable)
PROCESSOR SPECIFICATION			
	Mini	Pro	PrimeTouch
Operation	Listening only	Listening + minimum noise display and filter control	Listening + minimum noise display and maximum filter control
Filters			
Hi pass	N/A	15, 60, 100, 200, 350, 500 Hz	0-5500Hz user selectable
Low pass	N/A	600, 100, 1500, 2000, 3500, 5000 Hz	N/A
Display			
Type	N/A	Graphic, 240 x 160 LCD	Resistive touch screen 100mm x 132mm
Display of leak noise	N/A	Minimum noise or log modes	Minimum dB values, max frequency
Suitable for use in sunlight	N/A	N/A	Yes
GPS position feature	N/A	N/A	No
Direct signal input	N/A	N/A	N/A
Internal memory	N/A	N/A	4GB
Leak noise data storage (internal memory)	N/A	N/A	WAV file
USB ports	N/A	N/A	2
Power			
Type	Nickel Metal Hydride (rechargeable)	Nickel Metal Hydride (rechargeable)	Nickel Metal Hydride (rechargeable)
Operating life	≥10 hours continuous use from full charge	≥10 hours continuous use from full charge	7 hours (recharge time 4 hours depending on temp)
Environmental			
Operating temperature	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C
Water ingress protection	IP65 (headphone cover attached)	IP65 (headphone cover attached)	IP53
Dimensions	140 x 82 x 32 mm	82 x 121 x 46 mm	205 x 205 x 90 mm
Weight	0.3kg	0.7kg	1.35kg

www.ovarro.com

Ovarro has a global network of offices and distributors. Visit our website to find your local office.

