



(PRIMELOG

A small, robust and submersible battery powered water data logger designed to meet a wide range of applications

VARIANTS	1F	1P	2	2i
No. of bi-directional flow channels	1	-	1	1
No. of uni-directional flow channels	2	-	2	2
No. of analogue options (V, mV or mA)	-	-	3	-
No. of internal pressure transducers	-	1	-	1

LOGGING

Memory size 2GB (500 million readings)

Memory storage Cyclic or start/stop

Data types: Daily, minimum, maximum and totals

Logging modeCount and eventSample intervals1 second – 24 hours

Batch programming Program/readback multiple loggers simultaneously

FLOW CHANNEL

Meter index Records daily meter index values

Combination metering Option to log two uni-directional meters into one data set

Max. pulse frequency* 1000Hz

* For full list of compatible flow meters, please

contact support.primayer@ovarro.com

Ability to power high energy pulse units Elster (HRP, DRP, BGP100 & PR7), Sensus (OPTO06, OD07, Actaris & Cyble5)

ANALOGUE CHANNEL

 Voltage range
 0-1V, 0-5V, 0-10V

 Current range
 0-10mA, 4-20mA

 Accuracy
 ±0.1%

 Resolution
 ±0.025% (12bit)

INTERNAL PRESSURE TRANSDUCER CHANNEL

 Pressure range
 0-20Bar

 AutoZero function
 Yes

 Accuracy
 ±0.1%

Connection Male quick release

GENERAL

Software PrimeWorks

Power Replaceable 3.6V lithium battery

Battery lifeUp to 5 yearsDimensions100x160x44mm

Ingress protection IP68

PC connection Rapid local USB communication cable

PART NUMBER		NXG-**	NXG-*	NXG-**	NXG-***
Model	PrimeLog+	40			
Variant	1F		1		
	1P		2		
	2		3		
	2i		4		
Pressure Bar range	10Bar (1P / 2i)			10	
	20Bar (1P / 2i)		20		
	Not Applicable (1F / 2				
Flow pin configuration	Standard				
	French				033

ENVIRONMENTAL

O°C to 60°C (internal pressure transducer models)
Operating Temperature
-10°C to 60°C (all other XiLog models)
Maximum Humidity
99% Relative Humidity
Dimensions
240x145x145mm
Ingress protection
IP68 (fully submersible to a depth of 1 metre)

REGULATORY COMPLIANCE

RoHS Directive EN 50581:2012

OVARRO,
CONNECTING
TECHNOLOGIES

WWW.ovarro.com

Ovarro has a global network of offices and distributors. Visit our website to find your local office.